

## VideoXpert™ Storage Server E-Series Enterprise 2U 18-Bay Rackmount

### Product Features

- Up to 288 TB of Raw Storage
- Intel® Xeon® Silver Scalable Processor
- Windows Server 2019 Operating System
- iDRAC features include:
  - Remote Management
  - Disaster Recovery
  - Critical Resource Monitoring
- SSD 24/7 Duty Cycle Drives
- Redundant Power
- RAID 6
- 5-Year, On-site, NBD, Keep Your Hard Drive Warranty



### Enterprise, High Performance, and Video Processing

Benefit from scalable storage performance and video processing with this Enterprise server. This 2U platform brings you scalability and performance to adapt to a variety of the most demanding and process-intensive video surveillance applications.

Up to 288 TB of raw storage allows for long-term video storage and archiving. Paired with the latest Intel® Xeon® Scalable processor, this provides high density storage with Enterprise throughput for the most demanding applications.

Better performance is provided with dual SSDs for accelerated boot and application load times. Remote management, provided by iDRAC, allows for constant system status and critical resource monitoring. RAID 6 storage, in addition to redundant 1100 W power supplies, provide system reliability and high availability, while a five-year, on-site, next business day, Keep Your Hard Drive warranty ensures peace of mind.

### Technical Specifications

#### System

Item	Description
Processors	(2) Intel® Xeon® Silver 4210 Scalable Processor (10 Cores, 20 Threads, 2.20 GHz)
Maximum storage	Up to 288 TB
Operating system	Windows Server 2019

Item	Description
Memory	32 GB (4x 8 GB)
RAID	OS RAID 1; Data RAID 6
Networking	(4) 1 GbE RJ45 Ports; (2) 10 GbE SFP+ Ports; (1) Dedicated iDRAC Port
USB(s)	Rear (2) USB 3.0, Front (2) USB 2.0, Internal (1) USB 3.0
Video outputs	(1) VGA
Warranty	5-Year, On-site, NBD, Keep Your Hard Drive Warranty

**Mechanical**

Item	Description
Form factor	2U Rackmount
Hard drive bays	(18) 3.5" SAS Hot Swappable Bays & (2) M.2 SSD Slots
Power supply(s)	(2) 1100 W (100-240 VAC) 80 Plus Platinum
Power information	Input Power 516 W / 1761 BTU/h - Max Potential Power 900 W / 2980 BTU/h
Operating temperature	(Min) 50°F - (Max) 95° F [(Min) 10°C - (Max) 35°C]
Operating humidity	5 ~ 90% (non-condensing)
Dimensions (WxDxH)	19" (482.6mm) x 29.7" (755mm) x 3.4" (86.8mm)
Maximum weight	73 lbs. (33.1kg)

**Throughput**

Model	Recording Throughput	Playback Throughput
VXS2-E SAS: 1GbE	Up to 700 Mbps <sup>1</sup>	Up to 175 Mbps
VXS2-E SAS: 10GbE	Up to 2500 Mbps	Up to 175 Mbps

<sup>1</sup>Requires a network switch line rate capable of performing continuously at 700 Mbps while connected to 1 GbE.

### Part Numbers (SKUs)

SKU	Description
VXS2-E168-N12S	VideoXpert Enterprise, E-Series VxStorage Server, Windows Server 2019, RAID 6, 168 TB raw capacity, 128.29 TB effective capacity, fourteen (14) 12 TB SAS drives
VXS2-E216-N12S	VideoXpert Enterprise, E-Series VxStorage Server, Windows Server 2019, RAID 6, 216 TB raw capacity, 171.06 TB effective capacity, eighteen (18) 12 TB SAS drives
VXS2-E288-N16S	VideoXpert Enterprise, E-Series VxStorage Server, Windows Server 2019, RAID 6, 288 TB raw capacity, 232.83 TB effective capacity, eighteen (18) 16 TB SAS drives



Pelco, Inc.  
625 W. Alluvial Ave., Fresno, California 93711 United States  
(800) 289-9100 Tel  
(800) 289-9150 Fax  
+1 (559) 292-1981 International Tel  
+1 (559) 348-1120 International Fax  
[www.pelco.com](http://www.pelco.com)

**⚠ WARNING: Cancer and Reproductive Harm -**  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).  
**⚠ ADVERTENCIA: Cáncer y Daño Reproductivo -**  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).  
**⚠ AVERTISSEMENT: Cancer et Troubles de**  
**l'appareil reproducteur - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).**

Pelco, the Pelco logo, and other trademarks associated with Pelco products referred to in this publication are trademarks of Pelco, Inc. or its affiliates. ONVIF and the ONVIF logo are trademarks of ONVIF Inc. All other product names and services are the property of their respective companies. Product specifications and availability are subject to change without notice.

© Copyright 2021, Pelco, Inc. All rights reserved.